

Product Data Sheet: SphereCel GF



SPHERE CEL®

LAMINATE BULKER

 Fiberglass-based laminate bulker

CHARACTERISTICS

- Very fast resin absorption
- Jointless overlapping
- For flat and twodimensional laminates
- Outstanding surface quality
- Excellent bonding with covering fiberglass layers

INDUSTRIES

- Marine: hulls, decks and structures of boats and yachts
- <u>Transportation:</u> parts and panels of cars, trailers, trucks and RVs
- Mass transit: interior and exterior of trains, light rail, buses, ferry
- <u>Leisure:</u> kayaks, surfboards, pools, bath tubs
- <u>Industrial</u>: architectural panels, fans, containers, tanks

PROCESSING

- Hand lay up
- Wet pressing
- Panel production

All tests carried out by independent laboratory. This information is provided in good faith and is subject to modifications without prior notification. It does not constitute a commitment, neither a contractual document. Carbon-Core Corp will not assume any liability from use or misuse of data presented herein. Assessment of suitability is the responsibility of end user only.

Mailing Address: PO Box 332, Keswick, VA 22947 Warehouse: 48 Zion Station Court, Troy VA 22947 Tel: 434-510-7115 info@carbon-core.com



Product Data Sheet: SphereCel GF

Product Description:	Non-woven core material				
Base material:	Glass veil, volumized with thermoplastic microspheres				
Thickness: (+/- 10%)	1.2 mm	2 mm	3 mm	4 mm	5 mm
Weight: (+/- 15%)	55 g/m²	65 g/m²	80 g/m²	95 g/m²	110 g/m ²
Width: (+ 40 / - 20 mm) Up to 300 cm possible	100 cm	100 cm	100 cm	100 cm	100 cm
Roll length:	100 m	70 m	50 m	40 m	35 m
Weight per roll: (approx.)	5.5 kg	4.6 kg	4.0 kg	3.8 kg	3.9 kg
Packaging:	Plastic bag				
Storage:	To be stored in original packaging, in well-ventilated rooms, at moderate temperature. Keep away from humidity.				

All tests carried out by independent laboratory. This information is provided in good faith and is subject to modifications without prior notification. It does not constitute a commitment, neither a contractual document. Carbon-Core Corp will not assume any liability from use or misuse of data presented herein. Assessment of suitability is the responsibility of end user only.

Mailing Address: PO Box 332, Keswick, VA 22947 Warehouse: 48 Zion Station Court, Troy VA 22947 Tel: 434-510-7115 info@carbon-core.com